

Comar AIS Display

comar SYSTEMS



Information that can be displayed by the CSD 200:

- Name of Vessel
- MMSI Number
- Position
- Speed (SOG)
- Course (COG)
- Type of Vessel
- Call Sign
- Heading
- Rate of Turn
- Navigational Status
- Vessel Dimensions
- Destination

CSD 200 features:

- Complete information from all AIS vessels within range
- Variable CPA parameters giving visual and audible alarm
- The ability to plot targets in real time on a chart background
- Tabular listing of vessels sorted by range or bearing
- Reception and transmission of messages dependent on model
- Zoom, pan, brightness, contrast, audible alarm

The CSD 200 is a dedicated colour AIS Display designed to display and control information from either the CSA 200 Class A Transponder or the CSB 200 Class B. All AIS equipped vessels within VHF range can be displayed on a radar like screen or on a worldwide background chart and with the addition of a C-Map chart cartridge targets can be overlaid onto a full colour detailed chart background.

Full initialisation and control over either transponder is available from simple menu setup screens.

CSD 200 VERSIONS

The CSD 200 is available with two versions of software to suit operation with either the CSA 200, Class A Transponder or the CSB 200, Class B Transponder.

Software changes and updates are uploaded via the SD card.

be aware be safe at sea



COMAR SYSTEMS LTD • Medina Court • Arctic Road • Cowes • Isle of Wight • PO31 7XD • UK
T +44 (0)1983 282400 F +44 (0)1983 280402 info@comarsystems.com www.comarsystems.com

AIS

